TEMPOMATIC 4 electronic tap

Ref. 440006

Integrated batteries, stopcock



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 440006

Deck-mounted electronic basin tap:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by 2 concealed screws.

PEX flexible with stopcock F3/8" and filter.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 440006

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS WWRAS W
Warranty	30 g

///---

ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Batteries integrated into the body of the tap



Integrated solenoid valve



© DELABIE https://www.delabie.com