TEMPOMATIC 4 electronic tap

Ref. 443526

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443526

Electronic basin tap for panels:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body L. 190mm.

Cap fixed in place by 2 concealed screws.

Installation for panels from 1 - 24mm.

Anti-blocking security.

Stopcock.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443526

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	190mm
Flow rate	3 lpm
Norms	ACS 🚇 🦫 SVGW
Warranty	30 gg
Repairability	50 g

... .. .

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing tan

