

# BINOPTIC electronic tap

Ref. 379D13

Mains supply



## DESCRIPTION

**BINOPTIC electronic tap - Ref. 379D13**





Cross wall electronic basin mixer:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Filters and solenoid valves M3/8".  
Chrome-plated brass body.  
Chrome-plated spout L.135mm for cross wall installation ≤ 190 mm.  
Cable for sensor, L. 1.20mm, flexibles and mounting all pass through the same hole.  
Anti-blocking security.  
Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 379D13**

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Spout length	135mm
Flow rate	3 lpm
Norms	ACS CE VWRAS
Warranty	30 YEAR WARRANTY

## ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  LED diagnostic aids
-  Independent IP65 electronic unit

