

TEMPOMIX time flow mixer

Ref. 795209



DESCRIPTION

TEMPOMIX time flow mixer - Ref. 795209

Cross wall single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation via the push-button.
Time flow ~7 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Chrome-plated solid brass body M $\frac{3}{4}$ ".
Filters and non-return valves.
Adjustable maximum temperature limiter.
Tamperproof cross wall control ≤ 220 mm.
Tamperproof fixed cross wall spout ≤ 230 mm.
System for fixing to the wall via anti-rotating pin, back-nut and connection clamp.
Threaded rods can be cut-to-size.
Chrome-plated metal control.
30-year warranty.

ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation





Solid brass, installation behind partition



Temperature selection

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795209

Connector	M $\frac{3}{4}$ "
Technology	Time flow
Length	230mm
Spout length	75mm
Flow rate	3 lpm
Norms	ACS  
Warranty	