PREMIX COMFORT

Ref. 731003

Group thermostatic mixing valve, mixed water 32°-42°C

DESCRIPTION

PREMIX COMFORT - Ref. 731003

Group thermostatic mixing valve for mixed water from 32° - 42°C:
Anti-scalding safety.
Regulates temperature variations.
Filters and non-return valves can be accessed from the outside without removing the mechanism.
Thermal shock with no specific lever needed (push-button on the control knob).
Interchangeable cartridge with thermo-reactive cell.
High-resistance chrome-plated brass body.
Maximum hot water temperature: 85°C.
Differential hot water / mixed water: 15°C minimum.
Pressure difference at the inlets: 1 bar maximum (0.5 bar recommended).
Minimum pressure / maximum: 1 - 10 bar (1 - 5 bar recommended).
Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).
Mixed water outlet at the top (purple ring).
For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.
Maximum temperature limiter, can be adjusted by the installer.
Reduced risk of scalding by limiting temperature at the point-of-use.
90 lpm - M1".
30-year warranty.

ADVANTAGES

- Automatic shut-off if cold water supply fails
- Temperature stability
- Accessible filters and non-return valves
- Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMFORT - Ref. 731003

Connector	M1"
Technology	Thermostatic
Height	80mm
Depth	23mm
Length	160mm
Flow rate	90 lpm
Norms	ACS
Warranty	30 YEAR WARRANTY