## TEMPOMIX time flow shower panel

Ref. 790305

Time flow single control



## **ADVANTAGES**



80% water savings



Temperature control on the mixer



Aluminium panel, brass controls

## **DESCRIPTION**

TEMPOMIX time flow shower panel - Ref. 790305

Time flow aluminium shower panel with fixed shower head:

Anodised aluminium shower panel for wall-mounted, exposed installation. Top inlet via inline stopcocks  $M\frac{1}{2}$ ".

TEMPOMIX shower mixer with adjustable maximum temperature limiter. Soft-touch operation.

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.

Concealed fixings.

Filters and non-return valves.

With soap dish.


Shower panel suitable for people with reduced mobility.

30-year warranty.

## **TECHNICAL CHARACTERISTICS**

**TEMPOMIX time flow shower panel - Ref. 790305** 

Connector	M½"
Technology	Time flow
Height	1,050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS 🗓 🔘
Warranty	30 E



© DELABIE https://www.delabie.com