

SECURITHERM shower panel

Ref. 792404

Electronic battery-operated thermostatic



DESCRIPTION

SECURITHERM shower panel - Ref. 792404

Electronic thermostatic shower panel:
 Large model stainless steel panel for surface mounting.
 Top inlet via in-line stopcocks, M $\frac{1}{2}$ ".
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Battery-operated with 223 6V Lithium battery.
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.
 Shuts off on demand or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate set at 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 With integrated soap dish.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792404

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  



ADVANTAGES



Total hygiene: operate without manual contact




Automatic anti-bacterial proliferation duty flush



Thermostatic temperature regulation



Instant shut-off if cold water fails



Warranty

