

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 493400

Mains supply (recessed unit)



### DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493400**

Wall-mounted electronic basin mixer:  
 230/6V recessed mains supply.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body L. 160mm.  
 Cap fixed in place by 2 concealed screws.  
 Stopcocks.  
 Wall-mounted.  
 Recessed inlets 1/2".  
 Top or bottom supply.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493400**

|              |                         |
|--------------|-------------------------|
| Supply       | 230/6V mains (recessed) |
| Connector    | 1/2"                    |
| Technology   | Electronic              |
| Spout length | 160mm                   |
| Flow rate    | 3 lpm                   |
| Norms        | ACS CE RoHS DVGW SVGW   |
| Warranty     | 30 YEAR WARRANTY        |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Anti-bacterial duty flush

