BINOPTIC MIX electronic mixer

Ref. 398MCHLH

Mains supply



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 398MCHLH

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexibles with filters and solenoid valves M%".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Side temperature control with long lever and adjustable maximum temperature limiter.

Drop height: 250mm for countertop washbasins.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



90% water savings



Hygiene: no manual contact



Diagnostic LED




Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 398MCHLH

230/12V mains supply
M3/8"
Electronic
250mm
185mm
3 lpm
CE ACS
30 g



© DELABIE https://www.delabie.com