

## TEMPOMATIC urinal valve

Ref. 428156

Electronic, battery-operated




### DESCRIPTION

TEMPOMATIC urinal valve - Ref. 428156

Cross wall electronic urinal valve:  
CR123 6V lithium battery-operated, electronic control unit with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".  
Cross wall installation  $\leq$  155 mm.  
Shock-resistant infrared presence detection sensor.  
Detection distance, time flow and flow rate can be adjusted during installation.  
Detection delay is 3 seconds.  
Automatic pre-rinse is possible.  
Time flow ~3 seconds, can be adjusted from 3 - 12 seconds.  
Hygienic duty flush every 24 hours after last use: prevents vacuums.  
Flow rate 0.3 L/sec. at 3 bar, can be adjusted.  
Wall plate flush to the wall.  
Threaded rod can be cut to size.  
Compatible with rain water.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428156

Supply	6V batteries
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	0.3 l/sec
Warranty	

### ADVANTAGES



Total hygiene: no manual contact



ECO time flow 3 seconds



Cross wall installation



Hygienic duty flush

