

# TEMPOFLUX time flow urinal valve

Ref. 778766

Time flow 7 seconds. For DELABIE DELTACÉRAM urinals.


## DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778766

Exposed time flow urinal valve:  
For DELABIE DELTACÉRAM urinals.  
Wall-mounted exposed installation.  
Soft-touch operation.  
Time flow pre-set at ~7 seconds.  
Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.  
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
Compatible with rain water.  
Complies with European standard EN 12541 (class II acoustic level).  
Chrome-plated solid brass body M $\frac{1}{2}$ ".  
With chrome-plated neck tube.  
Angled for recessed inlet.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778766

Connector	$\frac{1}{2}$ "
Technology	Time flow
Height	290mm
Flow rate	0.15 L/sec
Warranty	



## ADVANTAGES



Time flow 7 seconds



Soft-touch operation



Stopcock built-in to wall plate



Sleek design

