BLACK BINOPTIC electronic tap

Ref. 498035

Battery-operated, H. 250mm



DESCRIPTION

BLACK BINOPTIC electronic tap - Ref. 498035

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

Battery-operated with 123 6V Lithium batteries.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

Matte black chrome finish.

PEX flexible with filter and solenoid valve M%".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Drop height 250mm for countertop washbasins.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



90% water savings



Hygiene: no manual contact




LED diagnostic aid

TECHNICAL CHARACTERISTICS

BLACK BINOPTIC electronic tap - Ref. 498035

Supply	6V batteries
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Finish	Matte black chrome
Norms	ACS 🔊
Warranty	30 質 WARRANTY



© DELABIE https://www.delabie.com