## **TEMPOMATIC 5 electronic tap**

Ref. 449006

**Batteries** 



## **DESCRIPTION**

TEMPOMATIC 5 electronic tap - Ref. 449006

Deck-mounted electronic basin tap:

Operated by CR123 Lithium 6V batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated metal body.

PEX flexible F3/8" with stopcock and filter.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

## **ADVANTAGES**



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve




Battery-operated

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic tap - Ref. 449006

| Supply       | 6V batteries        |
|--------------|---------------------|
| Connector    | F3/8"               |
| Technology   | Electronic          |
| Drop height  | 74mm                |
| Spout length | 105mm               |
| Flow rate    | 3 lpm               |
| Finish       | Chrome-plated metal |
| Norms        | ACS                 |
| Warranty     | 30 g<br>WARRANTY    |
|              |                     |



© DELABIE https://www.delabie.com