TEMPOMATIC MIX 5 electronic basin mixer

Ref. 499000

Mains supply - recessed unit



DESCRIPTION ADVANTAGES

Deck-mounted electronic basin mixer:

230/6V recessed mains supply.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant flow straightener.

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 499000

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated metal body.

PEX flexibles F3/8" with stopcocks, filters and non-return valves.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Side temperature control with adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush




Recessed mains supply

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 499000

Supply	230/6V mains supply
Connector	F3/8"
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	ACS
Warranty	30 g



© DELABIE https://www.delabie.com