

# TEMPOMATIC MIX 5

## electronic basin mixer

Ref. 499100

Mains supply - recessed unit





### DESCRIPTION

**TEMPOMATIC MIX 5 electronic basin mixer - Ref. 499100**

Deck-mounted electronic basin mixer:  
 230/6V recessed mains supply.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated metal body.  
 PEX flexibles F3/8" with filters and non-return valves.  
 Fixing reinforced by two stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 5 electronic basin mixer - Ref. 499100**

|              |  |
|--------------|--|
| Supply       | 230/6V mains supply  |
| Connector    | F3/8"  |
| Technology   | Electronic   |
| Drop height  | 74mm   |
| Spout length | 105mm  |
| Flow rate    | 3 lpm  |
| Finish       | Chrome-plated metal  |
| Norms        |  <b>ACS</b> |
| Warranty     |             |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve

