

SECURITHERM thermostatic shower mixer

Ref. H9768TP

Thermostatic mixer without non-return valves



DESCRIPTION

SECURITHERM thermostatic shower mixer - Ref. H9768TP

SECURITHERM dual control thermostatic shower mixer. Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).

No risk of cross flow between hot and cold water.

Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

¼-turn ceramic head for flow rate adjustment.

Temperature control up to 43°C.

Maximum temperature limiter pre-set to 38°C.

Thermal shocks are possible without shutting off the cold water.

Flow rate limited to 9 lpm at 3 bar.

ERGO controls.

M½" shower outlet.

F¾" inlets with integrated filters.

Mixer with inline STOP/CHECK wall connectors M1/2" M3/4".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

ADVANTAGES



SECURITHERM: optimal anti-scalding safety



Maximum hygiene: no non-return valves






Securitouch thermal insulation prevents burns



Thermostatic: total temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic shower mixer - Ref. H9768TP

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer, no non-return valves
Length	260mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 
Warranty	
Repairability	