Recessed waterproof housing for BINOPTIC

Ref. 370PBOX

Batteries, kit 1/2

DESCRIPTION

Recessed waterproof housing for BINOPTIC - Ref. 370PBOX

Recessed waterproof housing for BINOPTIC 2, kit 1/2:
Battery-operated with CR123 Lithium 6V batteries.
Recessed waterproof housing:
- Collar with waterproof seal.
- Hydraulic connection from the exterior and maintenance from the front.
- Modular installation (rails, solid walls, panels).
- Compatible with walls from 10 to 120mm (whilst maintaining the minimum recessing depth of 83mm).
- Adaptable standard pipework or "pipe in pipe".
- Integrated stopcock and flow rate adjuster, filter and solenoid valve are accessible from the front.
- BINOPTIC 2 tap F½".
- Supplied in 2 kits: secured system purge without sensitive elements.
30-year warranty.
Order with control plate references: 370106 or 370116.

ADVANTAGES

- Installation recessed in wall
- 6V Lithium batteries
- 100% waterproof housing

TECHNICAL CHARACTERISTICS

Recessed waterproof housing for BINOPTIC - Ref. 370PBOX

Connector	F½"
Height	150mm
Depth	83-190mm
Width	175mm
Norms	ACS
Warranty	30 YEAR WARRANTY