

# Control plate for TEMPOMATIC 4 for urinals

Ref. 430020

Recessed electronic mains supply valve - For urinals



## DESCRIPTION

Control plate for TEMPOMATIC 4 for urinals - Ref. 430020

TEMPOMATIC 4 electronic valve  $F\frac{1}{2}$ ", kit 2/2.  
Mains supply 230/6V (cable and transformer supplied).  
Solenoid valve enables opening and closing of water.  
White powder-coated stainless steel finish wall plate 145 x 145mm with integrated electronics.  
Shock-resistant infrared presence detection sensor.  
Detection delay is 10 seconds.  
3 programmes (rinsing volume can be adjusted according to urinal type).  
High frequency mode (exclusive to DELABIE):  
- Short rinse after each user.  
- Additional rinse after the period of increased frequency of use.  
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vaccums.  
Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.  
TEMPOMATIC 4  $F\frac{1}{2}$ " valve compatible with sea water, rain water and grey water.  
Installation in waterproof housing with waterproof collar, transformer, filter and stopcock  
Suitable for people with reduced mobility.  
30-year warranty.  
Order with frame system references 543000 for urinals  $\varnothing$  35mm, 543000D for urinals with flexible  $\frac{1}{2}$ " or with recessed housing 430SBOX.

## TECHNICAL CHARACTERISTICS

Control plate for TEMPOMATIC 4 for urinals - Ref. 430020

Supply	230/6V mains supply
Technology	Electronic
Length	145mm
Width	145mm
Finish	White powder-coated
Norms	     
Warranty	

## ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and high-frequency mode



Hygienic duty flush



Compatible with mains supply

