TEMPOFIX 3 self-supporting frame system for WCs

Ref. 564065

For time flow or battery-operated electronic valves - Ø 100mm



DESCRIPTION

TEMPOFIX 3 self-supporting frame system for WCs - Ref. 564065

Self-supporting frame system for wall-hung WCs, kit 1/2: Black powder-coated steel frame:

- With large feet for fixing to load-bearing floors.
- Frame height can be adjusted from 0 200mm (with 1m mark).
- Compatible with solid walls from 10 120mm.
- Ø 32mm flush tube with Ø 55mm connection washer.
- PVC soil pipe, Ø 100mm outlet to glue to waterproof seal, with 2 setting positions.

Recessed waterproof housing: for flush system without cistern, directly connected to pipework.

- Compatible with electronic or time flow WC valve.
- Compatible with CR123 6V Lithium batteries.
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate regulation.

Supplied pre-mounted.

30-year warranty.

Order with control plate references 464006, 464056, 465006, 465056, 763000, 763040 or 763041or 763030.

ADVANTAGES



Quick and easy to install: delivered pre-mounted



Space-saving



Adapt to wall thickness



Compatible with 6V Lithium batteries

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system for WCs - Ref. 564065

Connector	3/4"
Technology	Electronic and time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Diameter	Ø 100mm outlet
Finish	Black powder-coated steel
Warranty	30 E



