

TEMPOMATIC 5 electronic basin tap

Ref. 44900115

Mains supply



DESCRIPTION

TEMPOMATIC 5 electronic basin tap - Ref. 44900115

Basin-mounted electronic tap:
 230/6V recessed mains supply via plug.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated metal body.
 PEX flexibles M $\frac{1}{2}$ " with stopcocks, filters, non-return valves and conical inlets \varnothing 15mm.
 Fixing reinforced by two stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic basin tap - Ref. 44900115

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ " \varnothing 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	ACS  WRAS 
Warranty	

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Anti-bacterial proliferation duty flush
-  Integrated electronics and solenoid valve

