

TEMPOMATIC 5 electronic basin tap

Ref. 44900615

Battery-operated



DESCRIPTION

TEMPOMATIC 5 electronic basin tap - Ref. 44900615

Basin-mounted electronic tap:
 Operated by CR123 Lithium 6V batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated metal body.
 PEX flexibles M $\frac{1}{2}$ " with stopcocks, filters, non-return valves and conical inlets Ø 15mm.
 Fixing reinforced by two stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic basin tap - Ref. 44900615

Supply	6V batteries
Connector	M $\frac{1}{2}$ " Ø 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	ACS  WRAS 
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve



Battery-operated

