BINOPTIC 2 electronic tap

Ref. 373136

Batteries, deck-mounted, H. 100mm



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 373136

Deck-mounted chrome-plated matte black electronic basin tap: Operated by CR123 Lithium 6V batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use). Stainless steel tap, 100mm high for inset basins.

Sensor at the end of the spout optimises detection.

PEX flexible with filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth interior spout with low water volume (limits bacterial niches). Set detection distance, duty flush and launch thermal shocks manually. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 373136

Supply	6V batteries
Connector	M3/8"
Technology	Electronic
Drop height	100mm
Flow rate	3 lpm
Finish	Chrome-plated matte black
Warranty	30 g

ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids



© DELABIE https://www.delabie.com