BIOFIL 3-month shower head filter

Ref. 20361

Sterile



DESCRIPTION

BIOFIL 3-month shower head filter - Ref. 20361

DELABIE anti-Legionella and all-germ shower head filter.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: $0.1\mu m$ nominal and $0.2\mu m$ absolute sterilising grade.

Qualified water volume per duration of use: 9,000 litres.

Filtration flow rate: 6.2 lpm at 1 bar, 11.2 lpm at 3 bar and 13.2 lpm at 5 bar

(filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 3 months after installation.

Withstands thermal shocks: 70°C for 30 minutes.

Withstands chemical shocks: 100ppm of active chlorine for a cumulative total of 3 hours.

or 3 nours.

Sterile filter.

CE Class Is medical device.

Weight: Empty filter 133g; Full filter 259g.

Packaged individually. Must be ordered in quantities of 10.

Packaged in boxes of 10 units.

ADVANTAGES



Anti-Legionella and all-germ



Space saving



Lifespan: 3 months after installation



Quick to install without tools

TECHNICAL CHARACTERISTICS

BIOFIL 3-month shower head filter - Ref. 20361

Connector	M1/2"
Technology	Point-of-use filtration
Height	77mm
Length	194mm
Flow rate	6.2 lpm at 1 bar, 11.2 lpm at 3 bar and 13.2 lpm at 5 bar
Diameter	56mm
Lifespan	3 months
Norms	ACS WRAS BWGL CE

