

# SPORTING 2 SECURITHERM

## time flow shower panel

Ref. 714735

Thermostatic, scale-resistant nozzle


### DESCRIPTION

**SPORTING 2 SECURITHERM time flow shower panel - Ref. 714735**

Thermostatic time flow shower panel:  
Anodised aluminium and chrome-plated satin finish panel.  
Slimline structure with concealed fixings.  
Soft-touch operation.  
Automatic mechanical flush with each use.  
Time flow ~30 seconds.  
Flow rate 6 lpm at 3 bar.  
Tamperproof, scale-resistant fixed shower head with automatic flow rate regulation.  
Accessible filters and non-return valves.  
Integrated stopcocks.  
M $\frac{1}{2}$ " connection.  
Suitable for people with reduced mobility.  
30-year warranty.  
SECURITHERM technology:  
Thermostatic shower mixer directly integrated in the head of the shower panel.  
Temperature set by the installer.  
Stable temperature, pre-set at 38°C.  
Anti-scalding failsafe: automatic shut-off if the cold water fails.  
Anti-cold showers function: automatic shut-off if the hot water fails.

### TECHNICAL CHARACTERISTICS

**SPORTING 2 SECURITHERM time flow shower panel - Ref. 714735**

Connector	M1/2"
Technology	Time flow
Height	1020mm
Depth	16mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Warranty	



### ADVANTAGES



80% water savings



Automatic shut-off if cold water fails



Soft-touch operation



Sleek lines, concealed fixings

