

SPORTING 2 SECURITHERM AB

time flow shower panel

Ref. 714735AB

Thermostatic, AB system, scale-resistant nozzle


DESCRIPTION

SPORTING 2 SECURITHERM AB time flow shower panel - Ref. 714735AB

Thermostatic time flow shower panel:
Anodised aluminium and chrome-plated satin finish panel.
Slimline structure with concealed fixings.
Soft-touch operation.
Automatic mechanical flush with each use.
Time flow ~30 seconds.
Flow rate 6 lpm at 3 bar.
Tamperproof, scale-resistant fixed shower head with automatic flow rate regulation.
Accessible filters and non-return valves.
Integrated stopcocks.
AB anti-blocking system: water will flow only when the push-button is released.
M $\frac{1}{2}$ " connection.
Suitable for people with reduced mobility.
30-year warranty.
SECURITHERM technology:
Thermostatic shower mixer directly integrated in the head of the shower panel.
Temperature set by the installer.
Stable temperature, pre-set at 38°C.
Anti-scalding failsafe: automatic shut-off if the cold water fails.
Anti-cold showers function: automatic shut-off if the hot water fails.

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM AB time flow shower panel - Ref. 714735AB

Connector	M1/2"
Technology	Time flow
Height	1020mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Warranty	



ADVANTAGES



80% water savings



Automatic shut-off if cold water fails



Soft-touch operation



Sleek lines, concealed fixings

