SECURITHERM shower panel

Ref. 792400

Electronic battery-operated thermostatic



DESCRIPTION

SECURITHERM shower panel - Ref. 792400

Thermostatic electronic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With top inlet, via in-line stopcocks M½".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Battery-operated with 223 6V Lithium battery.
Infrared presence detection. Shower starts when hand is 4cm from the sensor.
Shuts off on demand or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate set at 6 lpm at 3 bar, can be adjusted.
Chrome-plated, tamperproof ROUND shower head.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
30-year warranty.


ADVANTAGES

- Total hygiene: operate without manual contact
- Automatic anti-bacterial duty flush
- Thermostatic temperature regulation
- Instant shut-off if cold water fails

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792400

Supply	6V battery
Connector	M½"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS BELGAQUA



Warranty	30 YEAR WARRANTY

© DELABIE