

Mechanical basin mixer

Ref. 2446

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever



DESCRIPTION

Mechanical basin mixer - Ref. 2446

Wall-mounted mechanical basin mixer.

Flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Securitouch thermal insulation prevents burns.

Body and spout with smooth interiors and low water volume (reduces bacterial development).

No non-return valves on the inlets.

Ø 40mm ceramic cartridge with pre-set maximum temperature limiter .

Body and spout with smooth interiors and low water volume (reduces bacterial development).Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Sculptured control lever.

Supplied with STOP/CHECK connectors M1/2" M3/4" ideal for hospitals.
30-year warranty.

ADVANTAGES



Smooth body/spout interior, reduces bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Ergonomic, sculptured control lever

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2446

Connector	M1/2"
Technology	Securitouch
Spout length	150mm
Flow rate	5 lpm
Finish	Chrome-plated brass
Norms	   
Warranty	
Repairability	

