

Angled grab bar 135°, Ø 25mm, 400 x 400mm

Ref. 5086P2

UltraPolish bright polished stainless steel, 2 fixing points



DESCRIPTION

Angled grab bar 135°, Ø 25mm, 400 x 400mm - Ref. 5086P2

Angled grab bar 135° for people with reduced mobility, Ø 25mm. For use as a handrail (horizontal part) or as a grab bar (135° part) for WCs, showers or baths.

Universal for either left or right side.

Dimensions: 400 x 400mm.

Bacteriostatic 304 stainless steel tube.

Stainless steel with UltraPolish bright polished finish, non-porous uniform surface for easy maintenance and hygiene.

Plate welded to the tube by invisible bead weld (process exclusive to ArN-Securit).

40mm gap between the bar and the wall: minimal space prevents the forearm passing between the bar and the wall, reducing the risk of fracture in case of loss of balance.

Concealed fixings, secured to wall by a 3-hole, 304 stainless steel plate, Ø 72mm.

Fixing plates and cover plates in 304 stainless steel.

Supplied with stainless steel screws for concrete walls.

Maximum recommended user weight: 115kg.

30-year warranty. CE marked.

TECHNICAL CHARACTERISTICS

Angled grab bar 135°, Ø 25mm, 400 x 400mm - Ref. 5086P2

Height	400mm
Length	400mm
Diameter	25mm
Width to the wall	40mm
Finish	UltraPolish 304 stainless steel, bright polished
Norms	 
Warranty	

ADVANTAGES



304 stainless steel: reduces bacterial development



For user weights up to 115kg



40mm gap between bar and wall: minimal space



UltraPolish: smooth surface, easy to clean

