

## Angled Nylon grab bar 135°, white, anti-bacterial, 220 x 220mm

Ref. 5083N

Bright white HR anti-bacterial Nylon, NylonClean, 3 fixing points







### DESCRIPTION

**Angled Nylon grab bar 135°, white, anti-bacterial, 220 x 220mm - Ref. 5083N**

Angled grab bar 135°, Ø 32mm, for people with reduced mobility.  
 Angled grab bar made from bright white HR Nylon.  
 For use as a handrail (horizontal part) or as a grab bar (135° part) for WCs, showers or baths.  
 NylonClean anti-bacterial treatment: optimal protection against bacterial and mould development.  
 Universal for either left or right side.  
 Suitable for intensive use in public places or the healthcare sector.  
 High strength polyamide (Nylon): with 2mm reinforced steel core treated against corrosion.  
 Uniform non-porous surface for easy maintenance and hygiene.  
 Good resistance to chemical products and cleaning.  
 Anti-UV treatment: prevents yellowing.  
 Warm to the touch.  
 38mm gap between the bar and the wall: minimal space prevents the forearm passing between the bar and the wall, reducing the risk of fracture in case of loss of balance.  
 3 fixing points prevent the hand from getting trapped and simplify installation. Concealed fixings secured by a 6-hole plate, Ø 72mm.  
 Supplied with stainless steel screws for concrete walls.  
 Dimensions: 220 x 220mm.  
 Tested to over 200kg. Maximum recommended user weight 135kg.  
 30-year warranty.  
 CE marked.


### ADVANTAGES

-  NylonClean anti-bacterial treatment
-  Tested to over 200kg
-  38mm gap from the wall: space saving
-  HR Nylon: smooth surface is easy to clean

### TECHNICAL CHARACTERISTICS

**Angled Nylon grab bar 135°, white, anti-bacterial, 220 x 220mm - Ref. 5083N**

Height	220mm
Length	220mm
Diameter	32mm
Width to the wall	38mm
Thickness	Nylon: 3.5mm; Steel: 2mm
Finish	HR anti-bacterial Nylon, bright white
Norms	 



---

Warranty

