

Mechanical basin mixer

Ref. 2721L

Single hole mechanical mixer H. 95mm L. 120mm



DESCRIPTION

Mechanical basin mixer - Ref. 2721L

Deck-mounted mechanical basin mixer.
 Single hole mixer with a curved spout H. 95mm L. 120mm fitted with hygienic flow straightener.
 Spout suitable for fitting a BIOFIL point-of-use filter.
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors (reduces bacterial development).
 No risk of cross flow between the hot and cold water.
 No non-return valves on the inlets.
 Thermal shocks are easy to undertake without removing the lever or shutting off the water supply.
 Flow rate regulated at 5 lpm.
 Hygiene control lever L. 150mm.
 Without pop-up waste.
 F3/8" PEX flexibles.
 Fixing reinforced via 2 stainless steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.
 Also available with copper tails.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2721L

Connector	F3/8"
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms	   
Warranty	
Repairability	

ADVANTAGES

- 
Hygiene: smooth interior reduces bacteria
- 
Maximum hygiene: low water volume
- 
Thermal shock without removing the control lever
- 
Hygiene lever: mixer requires no manual contact

