BIOCLIP mechanical basin mixer

Ref. 2821L

Single hole removable mechanical mixer H.95mm L.120mm, Hygiene lever





DESCRIPTION

BIOCLIP mechanical basin mixer - Ref. 2821L

Deck-mounted mechanical basin mixer.
BIOCLIP mechanical mixer: mixer can be removed entirely for cleaning and disinfection.
Single hole mixer with spout H. 95mm L. 120mm fitted with a BIOSAFE hygienic flow straightener.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
Body and spout with smooth interiors and low water volume.
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Flow rate regulated at 5 lpm.
Hygiene control lever L. 150mm.
Without pop-up waste.
Supplied with PEX flexibles PEX F3/8" with stopcocks in chrome-plated brass.
Fixing reinforced by 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.
Also available with copper tails.


ADVANTAGES

- Hygiene: remove for internal cleaning
- Hygiene: smooth interior reduces bacteria
- Pre-set maximum temperature limiter
- Hygiene lever: mixer requires manual contact

TECHNICAL CHARACTERISTICS

BIOCLIP mechanical basin mixer - Ref. 2821L

Connector	F3/8"
Technology	BIOCLIP removable mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS WRAS NF



Warranty	
Repairability	