

# Mechanical basin mixer

Ref. 2522L

Single hole mechanical mixer with swivelling spout H. 100mm L. 170mm



## DESCRIPTION

Mechanical basin mixer - [Ref. 2522L](#)

Deck-mounted mechanical basin mixer.

Single hole mechanical mixer with swivelling spout H. 100mm L. 170mm fitted with a hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 40mm classic ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Flow rate limited to 5 lpm at 3 bar.

Hygiene control lever L. 200mm.

PEX flexibles F3/8".

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

Mechanical basin mixer - [Ref. 2522L](#)

Connector	F3/8"
Height	267mm
Drop height	100mm
Spout length	170mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms

**ACS**



Warranty



Repairability

