

# Mechanical mixer for sinks or troughs

Ref. 2510L

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm






## DESCRIPTION

**Mechanical mixer for sinks or troughs - Ref. 2510L**

Deck-mounted mechanical sink mixer.  
Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.  
Spout suitable for fitting a BIOFIL point-of-use filter.  
Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.  
Body and spout with smooth interiors.  
No risk of cross flow between the hot and cold water.  
No non-return valves on the inlets.  
Body and spout made from chrome-plated brass.  
Hygiene control lever L. 200mm.  
Flow rate set at 9 lpm at 3 bar.  
Supplied with PEX flexibles F3/8".  
Fixing reinforced via 2 stainless steel rods.  
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Single hole mixer suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**Mechanical mixer for sinks or troughs - Ref. 2510L**

Connector	F3/8"
Height	302mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	  
Warranty	
Repairability	



## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



No manual contact thanks to Hygiene control lever



Comfort: optimum drop height and spout projection

