Mechanical mixer for sinks or troughs

Ref. 2510L

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm



Mechanical mixer for sinks or troughs - Ref. 2510L

Deck-mounted mechanical sink mixer.

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

 $\ensuremath{\text{\varnothing}}$ 40mm standard ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors.

Body and spout made from chrome-plated brass.

Hygiene control lever L. 200mm.

Flow rate set at 9 lpm at 3 bar.

Supplied with PEX flexibles F3/8".

Fixing reinforced via 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2510L

Connector	F3/8"
Height	302mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 😥 🗓
Warranty	30 g
Repairability	56 g



ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



No manual contact thanks to Hygiene control lever



Comfort: optimum drop height and spout projection

