## Mechanical mixer for sinks or troughs

Ref. 2210L

Single hole mechanical mixer with swivelling spout H. 145mm L. 215mm



Mechanical mixer for sinks or troughs - Ref. 2210L

Deck-mounted mechanical sink mixer.

Single hole mechanical mixer with swivelling spout H. 145mm L. 215mm fitted with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors.

Body and spout with chrome-plated brass.

Flow rate limited to 9 lpm at 3 bar.

Hygiene control lever L. 200mm.

Supplied with PEX flexibles F3/8".

Fixing reinforced via 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2210L

Connector	F3/8"
Length	215mm
Drop height	145mm
Spout length	225mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS OVER THE PROPERTY OF THE P
	ACS OVOW (I)



**ADVANTAGES** 



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



No manual contact thanks to hygiene control lever



Comfort: optimum drop height and spout projection

