TEMPOMATIC MIX PRO electronic mixer

Ref. 495253

Mains supply



DESCRIPTION

TEMPOMATIC MIX PRO electronic mixer - Ref. 495253

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods. PEX flexibles with filters and solenoid valves M%".

360° swivelling spout with smooth interior (reduces bacterial development). Removable spout for cleaning.

Anti-blocking security.

Side temperature control with ergonomic long lever and adjustable maximum temperature limiter.

Solenoid valves upstream of the mixing chamber.

Suitable for people with reduced mobility.

30-year warranty.

Two shut-off options on 230/12V models:

Standard mode: timed flow with automatic shut-off.

ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30

minutes of flow.

Thermal shocks are possible.

ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



Multiple modes of operation




Independent IP65 electronic control unit

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX PRO electronic mixer - Ref. 495253

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Norms	ACS OF CE
Warranty	30 gg



© DELABIE https://www.delabie.com