

TEMPOMATIC PRO electronic tap

Ref. 445253

Mains supply

DESCRIPTION

TEMPOMATIC PRO electronic tap - Ref. 445253

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.
PEX flexible with filter and solenoid valve M3/8".
360° swivelling spout with smooth interior (reduces bacterial development).
Removable spout for cleaning.
Anti-blocking security.
Two shut-off options:
Standard mode: timed flow with automatic shut-off.
ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.
Thermal shocks are possible.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC PRO electronic tap - Ref. 445253

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Norms	ACS  CE
Warranty	



ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



Multiple modes of operation



Anti-bacterial proliferation duty flush

