## TEMPOMATIC PRO electronic tap

Ref. 445257

**Battery-operated** 



## **DESCRIPTION**

**TEMPOMATIC PRO electronic tap - Ref. 445257** 

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

123 6V Lithium battery-operated.

Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods. PEX flexible with filter and solenoid valve M3/8".

360° swivelling spout with smooth interior (limits bacterial niches).

Removable spout for cleaning.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

Supply

## TECHNICAL CHARACTERISTICS

TEMPOMATIC PRO electronic tap - Ref. 445257

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Norms	ACS 😰 CE
Warranty	30 g
Repairability	50 g

611 hattony

## **ADVANTAGES**



Exceptional water savings: 85%




Hygiene: no manual contact



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush



© DELABIE https://www.delabie.com