

SECURITHERM thermostatic sink mixer

Ref. H9716

Single hole dual control tall mixer H. 225mm L. 200mm



DESCRIPTION

SECURITHERM thermostatic sink mixer - Ref. H9716

Deck-mounted SECURITHERM thermostatic dual control sink mixer. Tall, single hole mixer with swivelling tubular spout H. 225mm L.200mm with smooth interior. Spout with hygienic flow straightener, suitable for fitting a BIOFIL terminal filter. Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails. Scale-resistant thermostatic cartridge for adjusting the temperature. $\frac{1}{4}$ -turn ceramic head for adjusting the flow rate. Temperature can be adjusted, with two temperature limiters: first temperature limiter set at 38°C (can be overridden), and second temperature limiter set at 41°C. Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water. Flow rate limited to 9 lpm at 3 bar. ERGO control knobs. PEX flexibles F3/8" with filters and non-return valves. Fixing reinforced by 2 stainless steel rods. Thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic sink mixer - Ref. H9716

Connector	F3/8"
Technology	SECURITHERM thermostatic mixer
Drop height	225mm
Spout length	200mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	

