Mechanical basin mixer

Ref. 2506T1

Single hole mechanical mixer with swivelling spout H. 195mm L. 150mm



DESCRIPTION

Mechanical basin mixer - **Ref. 2506T1**

Deck-mounted mechanical basin mixer.
Single hole mechanical mixer with swivelling spout H. 195mm L. 150mm fitted with a BIOSAFE hygienic outlet.
Ø 35mm ceramic cartridge with maximum temperature limiter supplied but not installed.
Spout with smooth interior.
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Flow rate limited to 5 lpm at 3 bar.
Slimline control lever.
Stainless steel pop-up waste 1 1/4".
F3/8" PEX flexibles.
Fixing reinforced by 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- Hygiene: smooth interior reduces bacteria
- Hygiene: BIOSAFE hygienic outlet with no grid
- Ergonomic: slimline lever is easy to grip
- Comfort: optimised height and spout projection

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - **Ref. 2506T1**

Connector	F3/8"
Drop height	195mm
Spout length	150mm
Flow rate	5 lpm at 3 bar
Finish	Chrome-plated stainless steel
Norms	ACS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

