

Mechanical basin mixer

Ref. 2506T1

Single hole mechanical mixer with swivelling spout H. 195mm L. 150mm






DESCRIPTION

Mechanical basin mixer - Ref. 2506T1

Deck-mounted mechanical basin mixer.
Single hole mechanical mixer with swivelling spout H. 195mm L. 150mm fitted with a BIOSAFE hygienic outlet.
Ø 35mm ceramic cartridge with maximum temperature limiter supplied but not installed.
Spout with smooth interior.
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Flow rate limited to 5 lpm at 3 bar.
Slimline control lever.
Brass pop-up waste 1 1/4".
F3/8" PEX flexibles.
Fixing reinforced by 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2506T1

| | |
|---------------|---|
| Connector | F3/8" |
| Drop height | 195mm |
| Spout length | 150mm |
| Flow rate | 5 lpm at 3 bar |
| Finish | Chrome-plated stainless steel |
| Norms |    |
| Warranty |  |
| Repairability |  |



ADVANTAGES



Hygiene: smooth interior reduces bacteria



Hygiene: BIOSAFE hygienic outlet with no grid



Ergonomic: slimline lever is easy to grip



Comfort: optimised height and spout projection

