## Mechanical sink mixer

Ref. 2506T2

Single hole mechanical mixer with swivelling spout H. 220mm L. 200mm



## **ADVANTAGES**



Hygiene: smooth interior reduces bacteria



Hygiene: hygienic flow straightener with no grid



Ergonomic: slimline lever is easy to grip



Comfort: optimum drop height and spout projection

## **DESCRIPTION**

Mechanical sink mixer - Ref. 2506T2

Deck-mounted mechanical sink mixer.

Single hole mechanical sink mixer with swivelling, tubular spout H. 220mm L. 200mm fitted with a hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

 $\ensuremath{\text{\varnothing}}$  35mm ceramic cartridge with maximum temperature limiter supplied but not installed.

Spout with smooth interior.

Flow rate limited to 9 lpm at 3 bar.

Slimline control lever.

Without pop-up waste.

F3/8" PEX flexibles.

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.


Single hole mixer suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

Mechanical sink mixer - Ref. 2506T2

Connector	F3/8"
Drop height	220mm
Spout length	200mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 😥 🗓
Warranty	30 S WASRANTY
Repairability	50° E



© DELABIE https://www.delabie.com