

Mechanical mixer for sinks or troughs

Ref. 2565T3

Single hole, single control tall mixer with ceramic cartridge



DESCRIPTION

Mechanical mixer for sinks or troughs - Ref. 2565T3

Deck-mounted tall mechanical sink mixer.

Single hole, single control mixer with fixed spout H. 305mm L. 140mm.

Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors (reduced bacterial development).

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Thermal shocks are easy to undertake without removing control lever or shutting off the cold water.

Flow rate limited to 9 lpm at 3 bar.

Chrome-plated brass body and base.

Hygiene control lever L. 185mm requires no manual contact.

PEX flexibles F3/8".

Reinforced fixings by 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement or care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2565T3

Connector	F3/8"
Height	431mm
Drop height	305mm
Spout length	140mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms	ACS	WRAS	EN1717	B
Warranty	30 YEAR			
Repairability	50 YEARS			

ADVANTAGES



Hygiene: smooth interior reduces bacteria



Thermal shock without removing the control lever



Pre-set maximum temperature limiter



No manual contact thanks to Hygiene control lever

