

Mechanical mixer for sinks or troughs

Ref. 2565T3

Single hole, single control tall mixer with ceramic cartridge

DESCRIPTION







Mechanical mixer for sinks or troughs - Ref. 2565T3

Deck-mounted tall mechanical sink mixer.
 Single hole, single control mixer with fixed spout H. 305mm L. 140mm.
 Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
 Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors (reduced bacterial development).
 Thermal shocks are easy to undertake without removing control lever or shutting off the cold water.
 Flow rate limited to 9 lpm at 3 bar.
 Chrome-plated brass body and base.
 Hygiene control lever L. 185mm requires no manual contact.
 PEX flexibles F3/8".
 Reinforced fixings by 2 stainless steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement or care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS





Mechanical mixer for sinks or troughs - Ref. 2565T3

Connector	F3/8"
Height	431mm
Drop height	305mm
Spout length	140mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms	   
Warranty	
Repairability	



ADVANTAGES

-  Hygiene: smooth interior reduces bacteria
-  Thermal shock without removing the control lever
-  Pre-set maximum temperature limiter
-  No manual contact thanks to Hygiene control lever

