Mechanical basin mixer

Ref. 2446S

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever



DESCRIPTION

Mechanical basin mixer - Ref. 2446S

Wall-mounted mechanical basin mixer.

Swivelling, flat under-spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Securitouch thermal insulation prevents burns.

 $\ensuremath{\text{\varnothing}}$ 40mm ceramic cartridge and pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduce niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Sculptured control lever.

Supplied with standard connectors, M1/2" M3/4".

30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2446S

Connector	M1/2"
Technology	Securitouch
Spout length	150mm
Flow rate	5 lpm
Finish	Chrome-plated brass
Norms	ACS ON EN
Warranty	30 gg WARRANTY
Repairability	50° sepanality

ADVANTAGES



Smooth body/spout interior, reduces bacteria




Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Ergonomic, sculptured control lever



© DELABIE https://www.delabie.com