Mechanical basin mixer

Ref. 2446L

Wall-mounted mixer with swivelling spout L. 150, Hygiene lever L. 150



DESCRIPTION

Mechanical basin mixer - Ref. 2446L

Wall-mounted mechanical basin mixer.

Swivelling, flat under-spout L. 150mm in chrome-plated brass with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Securitouch thermal insulation prevents burns.

 \emptyset 40mm ceramic cartridge and pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduce niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm.

Supplied with STOP/CHECK connectors, M1/2" M3/4", ideal for hospitals. 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2446L

Connector	M1/2"
Technology	Securitouch
Spout length	150mm
Flow rate	5 lpm
Finish	Chrome-plated brass
Norms	ACS WRAS ON First 6-gylas Organisms
Warranty	30 S WASSANTY
Repairability	50 g

ADVANTAGES



Smooth body/spout interior, reduces bacteria




Pre-set maximum temperature limiter




Securitouch thermal insulation prevents burns



Hygiene control lever requires no manual contact





© DELABIE https://www.delabie.com