SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741S

Dual control thermostatic mixer



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741S

SECURITHERM dual control thermostatic shower mixer.

Mixer with anti-scalding failsafe: shuts off automatically if cold water supply

Prevents cold showers: shuts off automatically if hot water supply fails.

Securitouch thermal insulation to prevent burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4 -turn ceramic head for flow rate adjustment.

Temperature control from 25 - 41°C.

Double temperature limiter: 1st limiter set at 38°C can be overridden, 2nd limiter set at 41°C.

Thermal shocks are are easy to undertake without removing the control knob or shutting off the cold water.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and ERGO controls.

M1/2" shower outlet.

F3/4" inlets with integrated filters and non-return valves.

Wall-mounted mixer with M1/2" M3/4" off-set standard connectors.

Mixer ideal for healthcare facilities, retirement and care home, hospitals and clinics.

Mixer suitable for people with reduced mobility

Shower mixer with 30-year warranty.

ADVANTAGES



SECURITHERM: Optimum antiscalding safety



Double temperature limiter



Securitouch thermal insulation prevents burns





Thermostatic: complete temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741S

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer
Depth	84mm
Length	286mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
	ACS DOWN

















DELABIE

Warranty



© DELABIE https://www.delabie.com