

SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741S

Dual control thermostatic mixer







DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741S







SECURITHERM dual control thermostatic shower mixer.
 Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
 Prevents cold showers: shuts off automatically if hot water supply fails.
 Securitouch thermal insulation to prevent burns.
 Scale-resistant thermostatic cartridge for temperature adjustment.
 ¼ -turn ceramic head for flow rate adjustment.
 Temperature control from 25 - 41°C.
 Double temperature limiter: 1st limiter set at 38°C can be overridden, 2nd limiter set at 41°C.
 Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and ERGO controls.
 M1/2" shower outlet.
 F3/4" inlets with integrated filters and non-return valves.
 Wall-mounted mixer with M1/2" M3/4" off-set standard connectors.
 Mixer ideal for healthcare facilities, retirement and care home, hospitals and clinics.
 Mixer suitable for people with reduced mobility
 Shower mixer with 30-year warranty.

ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  Double temperature limiter
-  Securitouch thermal insulation prevents burns
-  Thermostatic: complete temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741S

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer
Depth	84mm
Length	286mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	     
Warranty	