SECURITHERM Securitouch thermostatic shower-bath mixer



Ref. H9752S

Dual control thermostatic shower mixer

DESCRIPTION

SECURITHERM Securitouch thermostatic shower-bath mixer - Ref. H9752S

SECURITHERM dual control thermostatic shower-bath mixer.
Mixer with anti-scalding safety: shuts off automatically if cold water supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic cartridge for temperature adjustment.
¼-turn ceramic head for flow rate adjustment.
Temperature control from 25 - 41°C.
Double temperature limiter: first limiter set at 38°C (can be overridden), second limiter set at 41°C.
Straight forward thermal shock procedure without removing the control knob or shutting off the cold water supply
Thermostatic mixer fitted with an automatic diverter with low pressure lock maintains the shower position even if the flow rate is too low.
Chrome-plated brass body and ERGO control knobs.
M1/2" shower outlet.
F3/4" inlets with integrated filters and non-return valves.
Mixer with M1/2" M3/4" offset standard wall connectors.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Shower mixer with 30-year warranty.

ADVANTAGES

- SECURITHERM: Optimum anti-scalding safety
- Double maximum temperature limiter
- Securitouch anti-scalding thermal insulation
- Thermostatic: total temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower-bath mixer - Ref. H9752S

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer
Width	286mm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS, BELGAQUA
Warranty	30 YEAR WARRANTY

