Sequential thermostatic shower mixer

Ref. H9640S

Thermostatic mixer with no non-return valves, top outlet



DESCRIPTION

Sequential thermostatic shower mixer - Ref. H9640S

SECURITHERM thermostatic sequential shower mixer.

Thermostatic sequential mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation). No risk of cross flow between hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic sequential cartridge for adjusting the flow rate and the temperature.

Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Body with smooth interior and low water volume (reduces niches where bacteria can develop).

Flow rate regulated at 9 lpm.

Chrome-plated brass body and Hygiene control lever L. 100mm.

3/4" top shower outlet.

Wall-mounted mixer with offset standard connectors, M1/2" M3/4".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics

Sequential mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: complete temperature stability

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H9640S

| Sequential thermostatic show | SECURITHERM Securitouch sequential |
|------------------------------|------------------------------------|
| Technology | thermostatic mixer |
| Width | 184mm |
| Flow rate | 9 lpm |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |
| Norms | ACS B |
| Warranty | 30 E WARRANTY |

